

**e-STUDIO™ 2500c/3500c/3510c**

Created for  
**BUSINESS,**  
focused on  
**COLOR**



**TOSHIBA**  
Don't copy. Lead.



The Toshiba e-STUDIO2500c, e-STUDIO3500c and e-STUDIO3510c are powerful, multifunction color copiers that combine the performance of a multifunction system with the quality of a professional graphics solution. Outstanding speed, performance, and professional-quality color as well as detailed text and graphics can be yours – everyday, all the time. Thanks to Toshiba proprietary print technology, the e-STUDIO2500c/3500c/3510c devices are the ideal, cost-effective graphic/business solution for even the busiest office and pay-for-print environments.

Multifunction  
COLOR



Full color output is produced at 25/35/35 PPM, with 35/35/45 PPM for black and white.



For the ultimate in flexibility — Print and scan, print and fax, even copy and scan — all at the same time.



Network Administration, 1,000 department codes and 10,000 user codes along with other security features.

SPECIFICATIONS

|   |   |
|---|---|
| <b>Copying Process</b>                  | 4-Drum Electrostatic Photographic Transfer System with Internal Transfer Belt   |
| <b>Copying Type</b>                     | 4-Beam Color Laser (8 bit)  |
| <b>Copy/Print Resolution</b>            | 600 x 600 dpi (2400 x 600 dpi B&W equivalent)   |
| <b>Copy/Print Speed</b>                 | e-STUDIO2500c – 25 PPM Color / 35 PPM B&W<br>e-STUDIO3500c – 35 PPM Color / 35 PPM B&W<br>e-STUDIO3510c – 35 PPM Color / 45 PPM B&W                                     |
| <b>Warm-Up Time</b>                     | Approx. 99 Seconds  |
| <b>First Copy Out Time</b>              | e-STUDIO2500c – 8.6 Seconds Color / 6.5 Seconds B&W<br>e-STUDIO3500c – 8.6 Seconds Color / 6.5 Seconds B&W<br>e-STUDIO3510c – 8.6 Seconds Color / 5.2 Seconds B&W       |
| <b>Duty Cycle</b>                       | 50,000/70,000/70,000 Copies   |
| <b>Multiple Copying</b>                 | Up to 999 Copies  |
| <b>Acceptable Paper Size and Weight</b> | Cassette: ST-R to LD (17 lbs. Bond - 90 lbs. Index)<br>Bypass: ST-R to 12" x 18" (17 lbs. Bond - 140 lbs. Index)<br>LCF: LT (17 lbs. - 28 lbs. Bond)                    |
| <b>Processor</b>                        | Power PC 867 MHz Shared   |
| <b>Memory (Min/Max)</b>                 | Main Memory: 512 MB / 1 GB<br>Page Memory: 256 MB / 512 MB<br>HD: 80+ GB  |
| <b>Reduction/Enlargement</b>            | 25% to 400%   |
| <b>Bypass</b>                           | 100-Sheet "Smart" Bypass (17 lbs. Bond - 140 lbs. Index)  |
| <b>Control Panel</b>                    | Color Half VGA Tilttable LCD Touch Panel  |
| <b>Paper Supply</b>                     | Up to 3,700-Sheet Input Capacity<br>Standard: 2 x 550-Sheet Cassettes<br>100-Sheet Bypass<br>Optional: 1 x 550-Sheet PFP, 1 x 550-Sheet Cassette<br>1 x 2,500-Sheet LCF |
| <b>Duplex</b>                           | Standard Trayless Automatic Duplex Unit   |
| <b>Dimensions</b>                       | Approx. 26" x 28" x 29" (W x D x H)   |
| <b>Weight</b>                           | Approx. 265 lbs.  |
| <b>Minimum Footprint Requirement</b>    | 39.53" x 28.31" (W x D)   |
| <b>PM Cycle</b>                         | 50,000/70,000/70,000  |
| <b>Drum Type/Yield</b>                  | Organic Photoconductor: 50,000/70,000/70,000  |
| <b>CMYK Toner Yield</b>                 | CMY: 21,000 / K: 24,000   |
| <b>Black Developer Yield</b>            | 50,000/70,000/70,000  |
| <b>Power Supply</b>                     | 115 V, 15 Amps  |
| <b>Power Consumption</b>                | Maximum 1.5 kW  |

PRINT SPECIFICATIONS

|                          |   |
|--------------------------|---|
| <b>PDL Support</b>       | PCL6 & PostScript 3   |
| <b>Operating Systems</b> | Netware 4.x, 5.x, 6.x, Windows Me/2000/XP, Windows NT 4.0, Windows Server 2003, Citrix MetaFrame, Macintosh, Linux, UNIX IPX/SPX, TCP/IP, EtherTalk, AppleTalk, NetBIOS Over TCP/IP LPR/LPD, IPP, SMB, SNMP, Netware, Port 9100, Bluetooth (HCRP) |
| <b>Protocol Support</b>  | Windows Me, 2000, Server 2003, XP, NT 4.0, Macintosh OS 8.6, 9.x, 10.1/10.2/10.3, UNIX, AS400 via iData & Port 9100, SAP R/3  |
| <b>Drivers</b>           | Windows Me, 2000, Server 2003, XP, NT 4.0, Macintosh OS 8.6, 9.x, 10.1/10.2/10.3, UNIX, AS400 via iData & Port 9100, SAP R/3  |
| <b>Connectivity</b>      | 10BaseT/100BaseTX Ethernet, 802.11b/g<br>Wireless LAN, USB, Bluetooth (HCRP)  |
| <b>Device Management</b> | TopAccess, Web Jetadmin   |
| <b>Certification</b>     | WHQL, Novell  |

SCAN SPECIFICATIONS

|                        |   |
|------------------------|---|
| <b>Scan Resolution</b> | 150 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi |
| <b>Scan Speed</b>      | 40 SPM Color / 50 SPM B&W                   |
| <b>File Format</b>     | TIFF, PDF, JPEG                             |
| <b>Authentication</b>  | LDAP, SMTP                                  |

FACSIMILE SPECIFICATIONS

|                            |   |
|----------------------------|---|
| <b>Compatibility</b>       | Super G3  |
| <b>Data Compression</b>    | MH/MR/MMR/JBIG  |
| <b>Transmission Speed</b>  | Approx. 3 Seconds Per Page                                  |
| <b>Fax Modem Speed</b>     | 33.6 Kbps   |
| <b>Fax Memory</b>          | 240 MB Transmission, 120 MB Reception                       |
| <b>Memory Transmission</b> | 100 Jobs, 1,000 Destinations Max.<br>400 Destinations / Job |
| <b>Scan Speed</b>          | .7 Seconds Per Page, 50 SPM                                 |

e-FILING SPECIFICATIONS

|                          |   |
|--------------------------|---|
| <b>Operation Method</b>  | Color Touch Screen Control Panel or Client PC                           |
| <b>Number of Boxes</b>   | 1 Public Box, 200 Private User Boxes                                    |
| <b>Capacity of Boxes</b> | 100 Folders Per Box, 400 Documents Per Folder<br>200 Pages Per Document |

OPTIONS

|   |  |
|---|--|
| <b>MR3018 RADF</b>                        | 100 Sheets   |
| <b>KD1018 Paper Feed Pedestal</b>         | 550-Sheet Pedestal, Statement-R to Ledger  |
| <b>MY1031 Cassette Module</b>             | 550-Sheet Drawer, Statement-R to Ledger  |
| <b>KD1019 Large Capacity Feeder (LCF)</b> | 2,500-Sheet Drawer, Letter   |
| <b>MJ1101 Multi-Position Finisher</b>     | Stationary Tray: 250 Sheets (Lt)<br>Tray 1 Stack Capacity: 2,000 Sheets (Lt)<br>Staple Capacity: 50 Sheets (Lt/Lt-R)         |
| <b>MJ1030 Saddle-Stitch Finisher</b>      | Tray 1 Stack Capacity: 1,000 Sheets (Lt)<br>Tray 2 Stack Capacity: 1,000 Sheets (Lt)<br>Staple Capacity: 50 Sheets (Lt/Lt-R) |
| <b>MJ6101 Hole Punch Unit</b>             | (for MJ1101) 2- or 3-Hole Punch Capability   |
| <b>MJ6004 Hole Punch Unit</b>             | (for MJ1030) 2- or 3-Hole Punch Capability   |
| <b>KN3500 Bridge Kit</b>                  | Required with MJ1101, MJ1030   |
| <b>GA1210 EFI Controller</b>              | (Not available at launch)  |
| <b>GD1210 Fax Board</b>                   |  |
| <b>GD1160 2nd Line Fax</b>                |  |
| <b>GN1041 Wireless LAN Adapter</b>        |  |
| <b>GN2010 Bluetooth Adapter</b>           |  |
| <b>GN3010 Wireless Antenna</b>            |  |
| <b>GP1060 Data Overwrite Kit</b>          |  |
| <b>GC1250 Main Expansion Memory</b>       |  |
| <b>GC1260 Page Expansion Memory</b>       |  |



Designs and specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates, based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.  
AUTHORIZED TOSHIBA DEALER

Corporate Office: 2 Musick, Irvine, CA 92618-1631  
 East Coast: 959 Route 46 East, 5th Floor, Parsippany, NJ 07054 / Tel: 973/316-2700 Fax: 973/263-2393  
 Midwest: 8770 W. Bryn Mawr Ave., Suite 700, Chicago IL 60631 / Tel: 773/380-6000 Fax: 773/380-8077  
 South: 4855 Peachtree Industrial Blvd., Suite 210, Norcross, GA 30092 / Tel: 770/209-8540 Fax: 770/209-8556  
 West Coast: 142 Technology, Suite 150, Irvine, CA 92618 / Tel: 949/462-6262 Fax: 949/462-2700  
 Web Site: www.copiers.toshiba.com or www.fax.toshiba.com